

# n: TER11-3115AVF SGR AV FLAT ANCHORS (flat head)



1. Unique identification code of the product-type:

Codice	Descrizione
<b>TER11-3115AVF</b>	TASSELLO 8 MM - LUNGH. 115
<b>TER11-3135AVF</b>	TASSELLO 8 MM - LUNGH. 135
<b>TER11-3155AVF</b>	TASSELLO 8 MM - LUNGH. 155
<b>TER11-3175AVF</b>	TASSELLO 8 MM - LUNGH. 175
<b>TER11-3195AVF</b>	TASSELLO 8 MM - LUNGH. 195
<b>TER11-3215AVF</b>	TASSELLO 8 MM - LUNGH. 215
<b>TER11-3235AVF</b>	TASSELLO 8 MM - LUNGH. 235

2. Numero di tipo, lotto, serie o qualsiasi altro elemento che consenta l'identificazione del prodotto da costruzione:

**THE BATCH NUMBER IS PRINTED ON THE PACKAGE ADD IN THE SINGLE PRODUCT**

3. Intended use of the construction product, in accordance with the relevant harmonized technical specification, as specified by the manufacturer:

**FASTENING OF THERMAL INSULATION TO THE WALL IN EXTERNAL INSULATION COMPOSITE SYSTEMS  
AS PER EAD 330196-01-0604**

4. Name, registered trade name or registered trademark, and address of the manufacturer:

**DAKOTA GROUP SAS  
Via Pitagora 3  
37010 Affi (VERONA) - ITALY**

5. System or systems of assessment and verification of constancy of performance of the construction product:

**SYSTEM 2\***


6. The notified body TZUS, TECHNICAL AND TEST INSTITUTE FOR CONSTRUCTION PRAGUE, number 1020, issued European Technical Assessment (ETA) 12/0571 based on EAD 330196 -01-0604 and has carried out the initial inspection of the production facility and factory production control (FPC), as well as the ongoing surveillance, assessment, and verification of the FPC in accordance with System 2+, issuing the factory production control certificate 1220-CPR-1669

7. Declared performance:

Characteristic resistance to tension loads for single anchor	kN	Specification
<b>Cat. A Concrete</b> - C 12/15 (EN 206-1) - C 16/20-C50/60 (EN 206-1)	0,95 1,4	EAD 330196-01-0604
<b>Cat. B Solid clay bricks (EN 771-1)</b>	1,4	EAD 330196-01-0604
<b>Cat. C Vertically perforated clay bricks (EN 771-1)</b>	0,75	EAD 330196-01-0604
<b>Cat. D LAC Lightweight aggregate concrete (EN 1520)</b>	0,6	EAD 330196-01-0604
<b>Cat. E Autoclaved aerated concrete AAC 4 (EN 771-4)</b>	1,1	EAD 330196-01-0604

8. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 7. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:  
Zeno Cipriani - Legal Representative  
Dakota Group S.a.S.

  
(Signature)

Brentino Belluno - 02-09-2024

(Place and Date)