

ALUMINUM AND TEXTILE RIDGE VENT ROLL



INDEX

- 1. Code Registry
- 2. Use
- 3. Technical Specification

1. CODE REGISTRY

Code	Description	Dimensions (m)	Weight	Pkg / Pallet
LUC70-9064	Aluminum and textile ridge vent roll	320 mm x 5 m	0,858 kg/pc.	4 pcs. / 120 pcs.
LUC70-9065	Aluminum and textile ridge vent roll	370 mm x 5 m	1,156 kg/pc.	4 pcs. / 96 pcs.

MATERIAL

Made of PP (polypropylene) and aluminum flashings.

2. USE

Used to improve ventilation of the ridge.

3. TECHNICAL SPECIFICATION

Specification	Description	Unity	Price
Dak.R.LUC70.906x	Supply and installation of ridge vent roll, central part in non-woven PP fabric, heatsealed to the "flashings" on the sides in aluminum or copper. Non-woven fabric has been sewn and glued, is equipped with a central reinforcement for easy fixing to the batten. Butyl strips on the bottom of flashings in aluminum or copper, make the installation easier ensuring adherence to the brick. Made of PP (polypropylene) and aluminum flashings. Used to improve ventilation of the ridge.		
Dak.R.LUC70.9064	320 mm x 5 m	pc.	-
Dak.R.LUC70.9065	370 mm x 5 m	pc.	-

