

STRAIGHT WIRE SUSPENSION Ø 4 FOLD



INDEX

1. Code registry
2. Description
3. Use
4. Features
5. Technical specification

1. REGISTRY CODE

Code	Description	Measures (mm)	Weight (kg/pcs.)*	Color	Pkg. / Pallet
GAN01-5124G	Straight suspension wire ø 4 bended type C - 125 mm	125	0,0163	Gray	100 pcs. / 37.800 pcs.
GAN01-5125G	Straight suspension wire ø 4 bended type C - 250 mm	250	0,0279	Gray	100 pcs. / 37.000 pcs.
GAN01-5126G	Straight suspension wire ø 4 bended type C - 375 mm	375	0,0395	Gray	100 pcs. / 28.000 pcs.
GAN01-5127G	Straight suspension wire ø 4 bended type C - 500 mm	500	0,0512	Gray	100 pcs. / 26.000 pcs.
GAN01-5128G	Straight suspension wire ø 4 bended type C - 750 mm	750	0,0745	Gray	100 pcs. / 28.800 pcs.
GAN01-5129G	Straight suspension wire ø 4 bended type C - 1000 mm	1000	0,0978	Gray	100 pcs. / 25.000 pcs.
GAN01-5130G	PStraight suspension wire ø 4 bended type C 1500 mm	1500	0,1443	Gray	100 pcs. / 28.000 pcs.
GAN01-5131G	Straight suspension wire ø 4 bended type C - 2000mm	2000	0,1909	Gray	100 pcs. / 28.000 pcs.
GAN01-5132G	Straight suspension wire ø 4 bended type C - 2500 mm	2.500	0,2374	Gray	100 pcs. / 28.000 pcs.
GAN01-5133G	Straight suspension wire ø 4 bended type C - 3000mm	3000	0,2840	Gray	100 pcs. / 10.500 pcs.

MATERIAL Made of drawn wire

* tolerance ±5% according EN10143

2. DESCRIPTION

Straight suspension wire with folded closed loop. A quick hook or butterfly spring can be mounted on the straight end.
Available in 10 sizes, from 125 mm to 3.000 mm. Reaction to fire Class A1

3. USE

Used for suspension of false ceilings and attaching metal structures to plasterboard.

STRAIGHT WIRE SUSPENSION Ø 4 FOLD

4. CARATTERISTICHE

Material	Made of drawn wire	-
Coating	Zinc - min Z100	EN 10327
Body thickness	4,00 mm	EN 10143
Load	0,50 kN	-
Reaction to fire	A1 Class	EN 14195
Durability	B Class	-
Box	100 pcs.	-

5. VOCI DI CAPITOLATO

Item	Description	Unit	Price
Dak.B.GAN01.51xxG	Straight suspension wire with folded closed loop. Available in 10 measures, from 125 mm to 3000 mm. Reacting to fire Class A1 Packaged in boxes by 100 pcs.. Made of drawn wire Used for suspension of false ceilings and attaching metal structures to plasterboard. o.		
Dak.B.GAN01.5124G	Straight suspension wire ø 4 fold type C - 125 mm.....	pcs.	-
Dak.B.GAN01.5125G	Straight suspension wire ø 4 fold type C - 250 mm.....	pcs.	-
Dak.B.GAN01.5126G	Straight suspension wire ø 4 fold type C- 375 mm.....	pcs.	-
Dak.B.GAN01.5127G	Straight suspension wire ø 4 fold type C- 500 mm.....	pcs.	-
Dak.B.GAN01.5128G	Straight suspension wire ø 4 fold type C - 750 mm.....	pcs.	-
Dak.B.GAN01.5129G	Straight suspension wire ø 4 fold type C- 1.000 mm.....	pcs.	-
Dak.B.GAN01.5130G	Straight suspension wire ø 4 fold type C -1.500 mm.....	pcs.	-
Dak.B.GAN01.5131G	Straight suspension wire ø 4 fold type C - 2.000 mm.....	pcs.	-
Dak.B.GAN01.5132G	Straight suspension wire ø 4 fold type C - 2.500 mm.....	pcs.	-
Dak.B.GAN01.5133G	Straight suspension wire ø 4 fold type C - 3.000 mm.....	pcs.	-