

MASKING-TAPE



INDEX

1. Code registry
2. Description
3. Use
4. Laying instructions
5. Specifications

1. CODE REGISTRY

Code	Description	Dimensions (mm)	Weight	Colour	Pkg. / Pallet
RET23-11020	Masking Tape	50 mm x 23 m	0,10 kg/pc.	-	20 pcs. / 840 pcs.
RET23-11019	Masking tape	50 mm x 75 m	0,25 kg/pc.	-	20 pcs. / 720 pcs.
RET23-11021	Masking Tape	50 mm x 150 m	0,50 kg/pc.	-	10 pcs. / 490 pcs.

MATERIAL                      Made of microperforated and folded sandpaper.

TEST:

• Fire resistance:

• Flexural strength    :

• Resistenza di snervamento:

• Dimensional stability:

performance not determined

performance not determined

5,239 N/mm

length:                      -0,1%

width:                      1,2%

STORAGE RULES:

Dry location with constant temperature between -10°C and +60°C.

2. DESCRIPTION

Roll of special sandpaper, microperforated and folded.  
Both sides were sanded in order to achieve better adhesion to the plasterboard filler used.  
The tape has been microperforated using an electrical device for better levelling when the plaster is applied.  
It is folded in the middle for easy positioning of the tape.

3. USE

Used to join straight or concave joints between plasterboard sheets (partition walls and ceilings).

4. LAYING INSTRUCTIONS

- •

•

•
- Make sure the working surface is clean (no dust or grease).

Use a smoothing trowel. Cover the area to be joined between the 2 plasterboards with 3 mm of levelling compound.

Apply micro-perforated paper. Remove excess levelling compound with the trowel. Cover with finishing compound.

Once dry, sand with an abrasive.

Temperature range: 5°C to 30°C.

5. TECHNICAL SPECIFICATION

Item	Description	Unit	Price
Dak.B.RET23-1102x	Supply and installation of special microperforated and folded abrasive masking tape for joining straight or concave joints between plasterboard sheets (partition walls and ceilings). Packaged in boxes. Made of decoloured long-fibre paper, treated against moisture.	pc.	-
Dak.B.RET23-11020	50 mm x 23 m.....	pc.	-
Dak.B.RET23-11019	50 mm x 75 m.....	pc.	-
Dak.B.RET23-11021	50 mm x 150 m.....	pc.	-