

ANTI-NOISE RUBBER SHIM



TER9-1123R



TER9-1143/GR



TER9-1147/G

INDEX

1. Code registry
2. Description
3. Use
4. Laying tips
5. Technical specification

1. CODE REGISTRY

Cose	Description	Measures (mm)	Weight	Pkg. / Pallet
TER09-1123/G	Anti-noise rubber 3mm thickness	Ø 110 - thickness 3	-	600 pc. / 5.400 pcs.
TER09-1143/G	Anti-noise rubber for Arkimede™	Ø 120 - thickness 2	0,04 kg/pc.	180 pc. / 8.100 pcs.
TER09-1147/G	Anti-noise rubber for Arkimede™ 10	Ø 157 - thickness 1	0,03 kg/pc.	120 pc. / 15.120 pcs.

MATERIAL TER09-1143/G e TER09-1147/G made of thermoplastic rubber (TPE). TER09-1123R made of rubber (EPDM)

2. DESCRIPTION

Anti-noise rubber for ARKIMEDE line.

- TER09-1143/G works with ARKIMEDE 18, 35, 41, 60 e 115 only Paving. Diameter 120 mm, thickness 2 mm. Not available for ARKIMEDE 10.
- TER09-1147/G works with ARKIMEDE 10 only, **both paving and decking**. Diameter 157 mm, thickness 1 mm.
- Model TER09-1123R is compatible with all Arkimedes™ models (except Arkimedes™ 10) for Paving and 3D-Scopic.

TER09-1147/G To be placed on terminal Support Arkimede 10 Decking (TER09-1147/1A), Arkimede 10 Paving (TER09-1147/4A2M and TER09-1147/4A4M) and Fixed Support for Quadrotti (TER09-1120)

3. USE

TER09-1143/G has to be placed on both the 3D-Scopic and ARKIMEDE Support heads for paving only

TER09-1147/G works on ARKIMEDE 10, both paving and decking. It reduces walkover noise.

TER09-1123R has to be placed on both the 3D-Scopic and ARKIMEDE Support heads for paving only (except for ARKIMEDE 10). It reduces walkover noise.

4. TECHNICAL SPECIFICATION

Item	Description	Unit	Price
Dak.O.TER09-11xx/x	Supply and installation of anti-noise rubber with the following characteristics: • Model TER09-1143/G is compatible with Arkimede™ 18, 35, 41, 60 and 115 in Paving version only. • Model TER09-1147/G is compatible only for Arkimede™ 10 both Paving and Decking. it is also compatible with the fixed support TER09-1120. • Model TER09-1123R is compatible with all Arkimede™ models (except Arkimede™ 10) for Paving and 3D-Scopic. High capacity > 300 ton/m2. Made of PE-HD (high-density polyethylene). For reinforcing and consolidating grass surfaces intended for car parking and/or play activities and/or outfitting.		
Dak.O.TER09-1123R	Measures Ø 110 - thickness 3 mm	pc.	-
Dak.O.TER09-1143/G	Measures Ø 120 - thickness 2 mm	cf.	-
Dak.O.TER09-1147/G	Measures Ø 110 - Ø 157 - thickness.....	cf.	-



OUTDOOR

