


HERCULES DECKING - SELF-LEVELING HEAD




INDEX

1. Code registry
2. Description
3. Use
4. Load test
5. Fields of use
6. Technical specification


1. CODE REGISTRY

Code	Description	Dimensions (mm)	Weight	Pkg / Pallet
TER09-1183/1L25	Self-Leveling Head Hercules for decking	from 25 to 37	0,22	30 pcs. / 720 pcs.
TER09-1183/1L37	Self-Leveling Head Hercules for decking	from 37 to 60	0,28	30 pcs. / 480 pcs.
TER09-1183/1L60	Self-Leveling Head Hercules for decking	from 60 to 94	0,40	25 pcs. / 300 pcs.
TER09-1183/1L94	Self-Leveling Head Hercules for decking	from 94 to 150	0,54	20 pcs. / 160 pcs.
TER09-1183/1L150	Self-Leveling Head Hercules for decking	from 150 to 270	0,73	15 pcs. / 120 pcs.
TER09-1183/PI20	Extension only for Hercules 150 - 270	h. 120	0,18	20 pcs. / 300 pcs.
TER09-1183CHI	Adjustment key for Hercules	-	0,20	1 pcs. / -


MATERIAL Made of PP (polypropylene).



TER09-1183/1L25







TER09-1183/1L37




TER09-1183/1L60

HERCULES DECKING - SELF-LEVELING HEAD



BACK BASE



SELF-LEVELING HEAD



TER09-1183/P120



TER09-1183/CHI

2. DESCRIPTION

Hercules adjustable support for outdoor flooring, with adjustable height from min. 25 to max. 390 mm (depending on the model used). Each pack contains the complete disassembled support with base, screw and self-levelling head (till 5%) for decking for fixing the joist. The head of the holder is equipped with integrated anti-noise rubber. Only the model from h. 150 to 270 mm can be extended by applying the specific extension h. 120 mm (TER09-1183 / P120). The finalization of the adjustment of the support takes place with the floor installed using the appropriate key.

3. USE

Used in external areas, terraces, pavements.
Operating temperature: from -40°C to +60°C.
The use of polishing and sanding machines is not recommended.

HERCULES DECKING - SELF-LEVELING HEAD

4. LOAD TEST

In-House Self-Regulated Test:

The support was subjected to an increasing load using a hydraulic press until initial failure occurred.

The test punch used to apply the load had a diameter of 150 mm.

The following are the certified average values:

Code	Conditions	Maximum load		
		[kN]	[kg]	[lbs]
TER09-1183/1L25	Half height	42,36	4.319,40	9.514,20
	Full height	19,76	2.015,70	4.440,00
TER09-1183/1L37	Half height	33,98	3.465,30	7.632,90
	Full height	15,65	1.596,40	3.516,40
TER09-1183/1L60	Half height	39,22	3.998,90	8.808,10
	Full height	22,624	2.307,00	5.081,40
TER09-1183/1L94	Half height	37,77	3.851,20	8.482,80
	Full height	18,05	1.841,20	4.055,40
TER09-1183/1L150	Half height	39,26	4.003,80	8.818,8
	Full height	18,128	1.848,50	4.071,60

5. FIELDS OF USE

Waterproof membrane, hard insulating panels, squids and solid and compact pose plans

6. TECHNICAL SPECIFICATION

Code	Description	Unit	Price
Dak.D.TER09.1183/1Lxxx	Supply and installation of adjustable support with self-leveling head "Hercules", for external decking. Dimensions from min. 25 to max. 390 mm (depending on the model used). Available in black colour Made of polypropylene Used in external areas, terraces, pavements.	pc.	-
Dak.D.TER09.1183/1L25	Hercules with self-leveling head from 25 to 37 mm and base diameter of 210 mm.....	pc.	-
Dak.D.TER09.1183/1L37	Hercules with self-leveling head from 37 to 60 mm and base diameter of 210 mm.....	pc.	-
Dak.D.TER09.1183/1L60	Hercules with self-leveling head from 60 a 94 mm and base diameter of 230 mm.....	pc.	-
Dak.D.TER09.1183/1L94	Hercules with self-leveling head from 94 a 150 mm and base diameter of 230 mm.....	pc.	-
Dak.D.TER09.1183/1L150	Hercules with self-leveling head from 150 a 270 mm and base diameter of 230 mm.....	pc.	-
Dak.D.TER09.1183/P120	Extension h.120mm in polypropylene compatible with Hercules support 150, TER09-1183/1F150	pc.	-
Dak.D.TER09.1283	Adjustment key for Hercules	pc.	-