

PLUVIAL TUBE Ø 80



INDEX

1. Data and Documentation
2. Description
3. Features
4. Specifications

1. DATA AND DOCUMENTATION

Code	Description	Measurements (m)	Weight	Colour	Pkg / Pallet
GRO02-3150M2	Tube ø 80 mm	2	7.00 kg/pc.	Brown	1 pc. (2 m) / 24 cf.
GRO02-3150M3	Tube ø 80 mm	3	10.20 kg/pc.	Brown	1 pc. (3 m) / 24 cf.
GRO02-3150R2	Tube ø 80 mm	2	6.00 kg/pc.	Copper	1 pc. (2 m) / 24 cf.
GRO02-3150R3	Tube ø 80 mm	3	9.00 kg/pc.	Copper	1 pc. (3 m) / 24 cf.

MATERIAL Made of UV-resistant PVC.

2. DESCRIPTION

The downpipe is an integral element of the rainwater harvesting system. Rainwater is channelled from the gutter and drained into the rain pipes. Whose diameter of 80 mm guarantees their effectiveness. PVC downpipes are light and flexible, and are resistant to temperature fluctuations and weather. They are fastened to the wall by means of a collar tightened around the pipe and anchored to the wall by means of dowels or crosses.

PLUVIAL TUBE Ø 80

3. FEATURES

GENERAL CHARACTERISTICS		Requirements		
Material	PVC			
Colour	CIELAB L, a, b	GRO02-3150M2 GRO02-3150M3 brown	GRO02-3150R2 GRO02-3150R3 copper	EN 12200
ΔE		Max 2.00		

DIMENSIONAL DATA	Units of Measurement	Value		Tolerance	
		GRO01-3100M2 GRO01-3150M3 brown	GRO01-3100R2 GRO01-3150M3 copper effect	GRO01-3100M2 GRO01-3150M3 brown	GRO01-3100R2 GRO01-3150M3 copper effect
Outer diameter	mm	80		+ 0,40	
Wall thickness	mm	1,60		± 0,10	
Weight per metre	g/m	610,00	640,00	± 51,00	± 60,00
SECTION					

PHYSICAL AND MECHANICAL CHARACTERISTICS	Test Conditions	Value	Method
Gloss	-	> 40	DIN 67530
Thermal shrinkage	100° 30 min. in the air	<3%	Method B EN ISO 2505
VICAT temperature (VST)	50° C/h 50N	≥ 75° C	EN ISO 2507

4. SPECIFICATION ITEMS

Entry	Description	Unit	Price
Dak.R.GRO02.3150xx	Supply and installation of 80 mm diameter downpipe. In sizes of 2 or 3 metres Made of UV-resistant PVC. Used for collecting rainwater from roofs and its disposal.		
Dak.R.GRO02.3150M2	Brown 2 m.....	cf.	-
Dak.R.GRO02.3150M3	Brown 3 m.....	cf.	-
Dak.R.GRO02.3150R2	Copper Effect 2 m.....	cf.	-
Dak.R.GRO02.3150R3	Copper Effect.....	cf.	-