

SPLICE TAPE



INDEX

1. Data and Documentation
2. Use
3. Features
4. Specifications

1. DATA AND DOCUMENTATION

Code	Description	Colour	Dimensions (mm)	Weight	Pkg. / Pallet
PRO22-0906	Jointing Tape	Grey	h. 100 x 20 m - 2 mm thick	30 kg/m ³	-

MATERIAL

Hot Melt Base Adhesive Side - Plastic Film Adhesive Covers

2. USE

Dark grey adhesive joint tape for use on underlay membranes and at joints with perimeter strip. It is recommended that it be laid without ironing!

It can also be used for taping membranes to walls

3. FEATURES

FEATURE	TEST METHOD	VALUE
THICKNESS mm	Interior	2 mm
DENSITY Kg/m ³	Interior	30
STANDARD COLOURS	DARK GREY MATT	
ACOUSTIC IMPROVEMENT OF THE PRODUCT R _w ACCORDING TO RESEARCH DATA IN OUR POSSIBILITY	UNI EN ISO 10140-3:2010	2 dB
DYNAMIC RIGIDITY MN/m ³	UNI EN 29052-1 : 1993	45
THERMAL CONDUCTIVITY	EN 12667 AVERAGE VALUE BASED ON LABORATORY CERTIFICATES AND DATA IN OUR POSSESSION	0.040 W/mK At 10° C
OPERATING TEMPERATURE	-20 +80° C	
RESISTANCE TO MOULD AND INSECTS	EXCELLENT	
DOES NOT CONTAIN CFC (FREON)	IN ACCORDANCE WITH LAW NO. 549 OF 28/12/93	
ADHESIVE SIDE	HOT MELT BASE	
ADHESIVE COVER	PLASTIC FILM	

SPLICE TAPE

4. SPECIFICATION ITEMS

Item	Description	Unit	Price
Dak.D.PRO22.0906	Supply and application of dark grey adhesive Jointing Tape, for use on undertile membranes and at joints with the perimeter strip. Dimensions h. 100 x 20 m - thickness 2 mm and grammage 30 kg/m ³	pcs.	-