



# UNDER PARQUET

## INDEX

1. Data and Documentation
2. Use
3. Features
4. Specifications

## 1. DATA AND DOCUMENTATION

| Code       | Description   | Colour | Dimensions (mm)              | Weight      | Pkg. / Pallet |
|------------|---------------|--------|------------------------------|-------------|---------------|
| PRO22-0912 | Under Parquet | White  | h. 1.250 x 25 m - 2 mm thick | 20/22 Kg/m3 | -             |

## MATERIAL

-

## 2. USE

Thermal-acoustic insulation, vapour barrier for floating floors and dry ceramic tiles, made of elasticised polyethylene foam and laminated with HD film.

## 3. FEATURES

|                                              |                                                                                            |
|----------------------------------------------|--------------------------------------------------------------------------------------------|
| Density (kg/m3)                              | 20 ÷ 22                                                                                    |
| Thermal Resistance ( $m^2K/W$ )              | 0,040                                                                                      |
| Maximum operating temperatures (°C)          | -20 +80                                                                                    |
| Compressive stress at 10 % strain (kPa)      | 13,002<br>Giordano Institute test report no. 192689 of<br>02/02/05 according to UNI EN 826 |
| Toxicity standards<br>AFNOR NF F 16-101-1988 | CSI Toxicity and Smoke Opacity Test Report No. DC01/494F05 of<br>07/07/05                  |

## 4. SPECIFICATION ITEMS

| Item             | Description                                                                                                                                                                                                                                                                   | Unit | Price |
|------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------|-------|
| Dak.D.PRO22.0912 | Supply and installation of a mat for thermal-acoustic insulation and vapour barrier function for floating floors and dry ceramic tiles, made of elasticised polyethylene foam and laminated with HD film.<br>Dimensions h. 1,250 x 25 m - thickness 2 mm, density 20/22 Kg/m3 | pcs. | -     |