

LIGHT ALUMINIUM UNDERLAY



INDEX

1. Data and Documentation
2. Use
3. Specifications

1. DATA AND DOCUMENTATION

| Code | Description | Dimensions (mm) | Weight | Pkg / Pallet |
|-------------|--------------------------|--------------------|-------------|-------------------|
| LUC70-9059 | Light Aluminium underlay | 300 mm x 10 m | 1.70 kg/pc. | 12 pcs. / 48 pcs. |
| LUC70-9059B | Light Aluminium underlay | 380 mm x 10 m | 1.96 kg/pc. | 12 pcs. / 48 pcs. |

MATERIAL

Made of PP (polypropylene) and aluminium pleats.

2. USE

Used to promote ridge ventilation.

3. SPECIFICATION ITEMS

| Entry | Description | Unit | Price |
|--------------------------|---|------|-------|
| Dak.R.LUC70.9059x | Supply and installation of under-layer in rolls, central body in polypropylene mesh thermally welded to the side pleated aluminium 'skirts'. The fabric mesh is sewn and glued, and has a central reinforcement to facilitate its attachment to the batten. The butyl strip on the intrados of the aluminium skirts facilitates installation by ensuring better adhesion to the brickwork. Made of PP (polypropylene) and aluminium pleats. Used to promote ridge ventilation. | | |
| Dak.R.LUC70.9059 | 300 mm x 10 m..... | pc. | - |
| Dak.R.LUC70.9059B | 380 mm x 10 m..... | pc. | - |