

FIXED VALVE WITH ADJUSTABLE DIFFUSER



INDEX

- 1. Data and Documentation
- 2. Use
- 3. Specifications

1. DATA AND DOCUMENTATION

Code	Description	Dimensions (mm)	Weight	Pkg. / Pallet
TER30-7160	Fixed Valve with Adjustable Diffuser without Mesh in ABS	ø 100	0.150 kg/pc.	10 pcs. / 340 pcs.
TER30-7161	Fixed Valve with Adjustable Diffuser without Mesh in ABS	ø 125	0.210 kg/pc.	10 pcs. / 340 pcs.
TER30-7162	Fixed Valve with Adjustable Diffuser without Mesh in ABS	ø 150	0.270 kg/pc.	10 pcs. / 200 pcs.

MATERIAL

Made of matt white-effect ABS, it is particularly resistant to weathering.

2. USE

It favours the recirculation of air between indoors and outdoors and the ventilation of rooms, limiting condensation and the formation of mould.

3. SPECIFICATION ITEMS

Entry	Description	Unit	Price
Dak.O.TER30.716x	Supply and installation of a fixed valve with adjustable diffuser made of matt white, consisting of a fixed inlet and an adjustable diffuser. Individually shrink-wrapped with barcode. Made of matt white ABS, it is particularly resistant to ageing due to exposure to atmospheric agents. It favours the recirculation of air between indoors and outdoors and the ventilation of rooms, limiting the phenomena of condensation and the formation of mould.		
Dak.O.TER30.7160	ø 100 mm	pc.	-
Dak.O.TER30.7161	ø 125 mm	pc.	-
Dak.O.TER30.7162	ø 150 mm	pc.	-

