

DK PLASTER S-GRID



INDEX

1. Code Registry
2. Use
3. Technical Specification

1. CODE REGISTRY

| Code | Product Description | Dimensions (m) | Weight | Colour | Pkg. / Pallet |
|------------|---------------------|----------------|-----------------------|--------|--|
| RET03-4060 | Dk Plaster S-Grid | 1,00 x 50 m | 65 gr./m ² | White | 50 m ² / 4.800 m ² |

MATERIAL Made of fiber glass Adfors Saint-Gobain (S46).

| Characteristics | Units Description | RET03-4050 | |
|---------------------------------|-------------------|------------|------|
| | | Warp | Weft |
| Setting | per 10 cm | 79 | 39 |
| Standard height | cm | 100 | |
| Roll length | m | 50 | |
| Treated Fabric Thickness | mm | 0,1 | |
| Loom state Fabric Weight | g/m ² | 65 | |
| LOI | % | 1 - 4 | |

Tolerances:

Height: ± 1%
Length: ± 2%
LOI: ± 3%

Packing:

The rolls of fabrics are packed vertically in a cardboard box, on a wooden pallet.

Storing:

Packed rolls are to be stored in dry rooms. Storing temperature is from -10 °C to +50°C.

2. USE

Used for the renovation of plasterboard walls or ceilings and as reinforcement for plaster and drywalls.

3. TECHNICAL SPECIFICATION

| Specification | Description | Unity | Price |
|-------------------------|--|----------------|-------|
| Dak.B.RET03.4060 | Supply and installation of White fiber glass mesh recommended for the renovation of large lesions and cracks in walls or plaster ceilings. It is the ideal solution for repairing a new plasterboard extremely damaged or to be used with normal compound for dry systems. Dimensions: height 1,00 x 50 m. Packed in cellophane rolls. Made of fiber glass Adfors Saint-Gobain (S46). Used for the renovation of plasterboard walls or ceilings and as reinforcement for plaster and drywalls. | m ² | - |