

SELF-ADHESIVE SEALING TAPE



INDEX

- 1. Code Registry
- 2. Use
- 3. Technical specification

1. CODE REGISTRY

Code	Description	Dimensions (mm)	Weight	Colour	Pkg. / Pallet
RET21-108010	Self-adhesive sealing tape	a 10 x 12.500 - thick. 1,5 - 3,0	4,70 kg/box	Light grey	30 pcs. / 16 box
RET21-108015	Self-adhesive sealing tape	a 15 x 12.500 - thick. 1,5 - 3,0	4,40 kg/box	Light grey	20 pcs. / 24 box
RET21-108020	Self-adhesive sealing tape	a 20 x 12.500 - thick. 1,5 - 3,0	4,50 kg/box	Light grey	15 pcs. / 32 box
RET21-108510	Self-adhesive sealing tape	a 10 x 7.500 - thick. 2,0 - 6,0	2,80 kg/box	Light grey	30 pcs. / 16 box
RET21-108515	Self-adhesive sealing tape	a 15 x 7.500 - thick. 2,0 - 6,0	2,60 kg/box	Light grey	20 pcs. / 24 box
RET21-108520	Self-adhesive sealing tape	a 20 x 7.500 - thick. 2,0 - 6,0	2,70 kg/box	Light grey	15 pcs. / 32 box
RET21-109015	Self-adhesive sealing tape	a 15 x 5.000 - thick. 5,0 - 9,0	5,70 kg/box	Light grey	20 pcs. / 24 box
RET21-109020	Self-adhesive sealing tape	a 20 x 5.000 - thick. 5,0 - 9,0	3,65 kg/box	Light grey	15 pcs. / 32 box
RET21-109025	Self-adhesive sealing tape	a 25 x 5.000 - thick. 5,0 - 9,0	3,60 kg/box	Light grey	12 pcs. / 40 box
RET21-109520	Self-adhesive sealing tape	a 20 x 3.250 - thick. 7,0 - 14,0	2,60 kg/box	Light grey	15 pcs. / 32 box
RET21-109525	Self-adhesive sealing tape	a 25 x 3.250 - thick. 7,0 - 14,0	4,00 kg/box	Light grey	12 pcs. / 40 box
RET21-109530	Self-adhesive sealing tape	a 30 x 3.250 - thick. 7,0 - 14,0	4,00 kg/box	Light grey	10 pcs. / 48 box

MATERIAL

Made of PU foam, polyacrylate adhesive.

CERTIFICATION

BG2 for external use if not directly exposed to UV rays, it is vapor permeable (DIN 18542).

2. USE

Used for the air-proof and waterproof sealing at the joints of windows, doors and sills. It is also useful for the protection from noise, dust, moisture and heat loss.











SELF-ADHESIVE SEALING TAPE

3. TECHNICAL SPECIFICATION

Specification	Description	Unity	Price
Dak.B.RET21.10xxxx	Supply and installation of sealing tape, self-adhesive and pre-stressed for sealing. Packed in boxes. Made of PU foam, polyacrylate adhesive. Used for the air-proof and waterproof sealing at the joints of windows, doors and sills. It is also useful for the protection from noise, dust, moisture and heat loss.		
Dak.B.RET21.108010	Dimension: a 10 x 12.500 - thick. 1,5 - 3,0 mm	box	-
Dak.B.RET21.108015	Dimension: a 15 x 12.500 - thick. 1,5 - 3,0 mm.	box	-
Dak.B.RET21.108020	Dimension: a 20 x 12.500 - thick. 1,5 - 3,0 mm.	box	-
Dak.B.RET21.108510	Dimension: a 10 x 7500 - thick. 2,0 - 6,0 mm	box	-
Dak.B.RET21.108515	Dimension: a 15 x 7.500 - thick. 2,0 - 6,0 mm	box	-
Dak.B.RET21.108520	Dimension: a 20 x 7.500 - thick. 2,0 - 6,0 mm	box	-
Dak.B.RET21.109015	Dimension: a 15 x 5.000 - thick. 5,0 - 9,0 mm	box	-
Dak.B.RET21.109020	Dimension: a 20 x 5.000 - thick. 5,0 - 9,0 mm	box	_
Dak.B.RET21.109025	Dimension: a 25 x 5.000 - thick. 5,0 - 9,0 mm	box	-
Dak.B.RET21.109520	Dimension: a 20 x 3.250 - thick. 7,0 - 14,0 mm	box	-
Dak.B.RET21.109525	Dimension: a 25 x 3.250 - thick. 7,0 - 14,0 mm	box	-
Dak.B.RET21.109530	Dimension: a 30 x 3.250 - thick. 7,0 - 14,0 mm	box	-

