

# HAMMERING ANCHOR



## INDEX

1. Code Registry
2. Use
3. Technical specification

## 1. CODE REGISTRY

Code	Description	Dimensions (mm)	Weight	Colour	Pkg. / Pallet
TER11-2325	Hammering anchor	ø 5 x 27	1,0 kg./box.	White	200 pcs. / - pcs.
TER11-2327	Hammering anchor	ø 6 x 37	1,0 kg./box.	White	200 pcs. / - pcs.
TER11-2329	Hammering anchor	ø 8 x 80	300 gr./box.	White	50 pcs. / - pcs.

### MATERIAL

Made of galvanized steel and plastic fischer.

## 2. USE

Used for the wall fixing of the starting track.  
We recommend to place it every 300 mm.

## 3. TECHNICAL SPECIFICATION

Specification	Description	Unity	Price
<b>Dak.B.TER11.232x</b>	Supply and installation of Hammering anchor with steel nail for fixing the starting track. Made of galvanized steel and plastic fischer. Used for the wall fixing of the starting track. We recommend to place it every 300 mm.		
<b>Dak.B.TER11.2325</b>	Dimension ø 5 x 27 mm.....	pcs.	-
<b>Dak.B.TER11.2327</b>	Dimension ø 6 x 37 mm.....	pcs.	-
<b>Dak.B.TER11.2329</b>	Dimension ø 8 x 80 mm.....	pcs.	-